

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.05.2019

Version number 20

Revision: 06.05.2019

**SECTION 1: Identification of the substance/mixture and of the company/
undertaking**

- **1.1 Product identifier**
- **Trade name: Spezial-Faserbetonkleber Nr. 12/56 c (B-Komp.)** _____
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Hardening agent/ Curing agent
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Obernolte Reent GmbH & Co. KG
Ravensberger Str. 63
32278 Kirchlegern

- **Informing department:**
Herr Obernolte
Tel.: ++49 (0)5223/9737-0

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS07

- Skin Irrit. 2 H315 Causes skin irritation.
- Eye Irrit. 2 H319 Causes serious eye irritation.
- Skin Sens. 1 H317 May cause an allergic skin reaction.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms** GHS07
- **Signal word** Warning

- **Hazard-determining components of labelling:**
3-aminomethyl-3,5,5-trimethylcyclohexylamine
triethylenetetramine
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with triethylenetetramine
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine
- **Hazard statements**
H315 Causes skin irritation.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.05.2019

Version number 20

Revision: 06.05.2019

Trade name: Spezial-Faserbetonkleber Nr. 12/56 c (B-Komp.)

(Contd. of page 1)

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

- **Precautionary statements**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves / eye protection / face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**

- **Description:** modified polyamidoamine

- **Dangerous components:**

| | | |
|---------------|----------------|---------|
| CAS: 100-51-6 | Benzyl alcohol | 2.5-10% |
|---------------|----------------|---------|

| | | |
|-------------------|--|--|
| EINECS: 202-859-9 | ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319 | |
|-------------------|--|--|

| | | |
|---------------|----------------------|-------|
| CAS: 112-24-3 | triethylenetetramine | <2.5% |
|---------------|----------------------|-------|

| | | |
|-------------------|--|--|
| EINECS: 203-950-6 | ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412 | |
|-------------------|--|--|

| | | |
|----------------|--|-------|
| CAS: 2855-13-2 | 3-aminomethyl-3,5,5-trimethylcyclohexylamine | <2.5% |
|----------------|--|-------|

| | | |
|-------------------|--|--|
| EINECS: 220-666-8 | ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412 | |
|-------------------|--|--|

| | | |
|-----------------|--|-------|
| CAS: 38294-64-3 | 4,4'-Isopropylidendiphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine | <0.5% |
|-----------------|--|-------|

| | | |
|--|--|--|
| | ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ⚠ Skin Sens. 1, H317; Aquatic Chronic 3, H412 | |
|--|--|--|

- **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**

- **General information**

Instantly remove any clothing soiled by the product.

Personal protection for the First Aider.

It is possible to choke in case of vomiting in unconsciousness.

Bring unconscious persons into a stable position on side.

Keep the respiratory tract free (remove dentures and vomiting).

(Contd. on page 3)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.05.2019

Version number 20

Revision: 06.05.2019

Trade name: Spezial-Faserbetonkleber Nr. 12/56 c (B-Komp.)

(Contd. of page 2)

Check the pulse. In case of heart failure you have to make a cardiac massage. In case of stoppage of breathing: artificial respiration.

Take up a doctor immediately!

- **After inhalation**

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness bring patient into stable side position for transport.

- **After skin contact**

Instantly wash with water and soap and rinse thoroughly.

Change immediately contaminated clothes.

- **After eye contact**

Rinse opened eye for several minutes under running water. Then consult doctor.

- **After swallowing**

Do not induce vomiting; instantly call for medical help.

Show the pack or the label to the doctor.

- **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

- **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**

- **Suitable extinguishing agents**

CO₂, extinguishing powder or water jet. Fight larger fires with water jet.

- **5.2 Special hazards arising from the substance or mixture**

Formation of poisonous gases during heating or in fires.

In case of strong heat burst- and explosion hazard, the pressure in the container will increase. In case of fire chill the container with water-spray.

- **5.3 Advice for firefighters**

- **Protective equipment:** Wear self-contained breathing apparatus.

- **Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Follow the emergency-plan.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**

Bring persons out of danger.

Wear protective equipment. Keep unprotected persons away.

- **6.2 Environmental precautions:**

Do not allow product to reach sewage system or water bodies.

- **6.3 Methods and material for containment and cleaning up:**

Ensure adequate ventilation.

- **6.4 Reference to other sections**

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

GB

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.05.2019

Version number 20

Revision: 06.05.2019

Trade name: Spezial-Faserbetonkleber Nr. 12/56 c (B-Komp.)

(Contd. of page 3)

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
Keep away from children.
- **Information about protection against explosions and fires:**
No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Information about storage in one common storage facility:**
Please follow the rules of the VCI-Storage-Concept for chemicals.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in a locked cabinet and out of the reach of children.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical systems:**
It must be possible to wash the skin in the working area.
Eye-wash bottle must be available.
- **8.1 Control parameters**
- **Components with critical values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:**
The lists that were valid during the compilation were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment**
- **General protective and hygienic measures**
The usual precautionary measures should be adhered to in handling the chemicals.
Instantly remove any soiled and impregnated garments.
Avoid contact with the eyes and skin.
Be sure to clean skin thoroughly after work and before breaks.
- **Breathing equipment:** Not required.
- **Protection of hands:** Hand Protection: Nitril-rubber-latex-gloves.
- **Material of gloves**
Butyl rubber II R: Thickness $\geq 0,5\text{mm}$; Break through time $\geq 480\text{ min}$
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Safety glasses
- **Body protection:** Protective work clothing.

GB

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.05.2019

Version number 20

Revision: 06.05.2019

Trade name: **Spezial-Faserbetonkleber Nr. 12/56 c (B-Komp.)**

(Contd. of page 4)

SECTION 9: Physical and chemical properties· **9.1 Information on basic physical and chemical properties**· **General Information**· **Appearance:**

| | |
|---------|------------------------------------|
| Form: | Fluid |
| Colour: | According to product specification |
| Smell: | Characteristic |

· **Change in condition**

| | |
|--|----------------|
| Melting point/freezing point: | Not determined |
| Initial boiling point and boiling range: | Not determined |

| | |
|--------------|----------------|
| Flash point: | Not applicable |
|--------------|----------------|

| | |
|----------------------|------------------------------|
| Self-inflammability: | Product is not selfigniting. |
|----------------------|------------------------------|

| | |
|-----------------------|---------------------------|
| Explosive properties: | Product is not explosive. |
|-----------------------|---------------------------|

| | |
|---------|---------------|
| Density | not determine |
|---------|---------------|

· **Solubility in / Miscibility with**

| | |
|-----------------------|--|
| Water: | Not miscible or difficult to mix |
| 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity· **10.1 Reactivity** No further relevant information available.· **10.2 Chemical stability**· **Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

· **10.3 Possibility of hazardous reactions** Reacts with strong acids and oxidizing agents· **10.4 Conditions to avoid** No further relevant information available.· **10.5 Incompatible materials:** No further relevant information available.· **10.6 Hazardous decomposition products:**

No dangerous decomposition products known

SECTION 11: Toxicological information· **11.1 Information on toxicological effects**· **Acute toxicity** Based on available data, the classification criteria are not met.· **LD/LC50 values that are relevant for classification:****100-51-6 Benzyl alcohol**

Oral LD50 1,570 mg/kg (rats)

Inhalative LC50 11 mg/l

112-24-3 triethylenetetramine

Oral LD50 1,716.2 mg/kg (rats)

Dermal LD50 1,465.4 mg/kg (rabbit)

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Oral LD50 1,030 mg/kg (rats)

(Contd. on page 6)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.05.2019

Version number 20

Revision: 06.05.2019

Trade name: **Spezial-Faserbetonkleber Nr. 12/56 c (B-Komp.)**

(Contd. of page 6)

- | | |
|---|-----------------|
| · 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA | Void |
| · 14.3 Transport hazard class(es) · ADR, ADN, IMDG, IATA · Class | Void |
| · 14.4 Packing group · ADR, IMDG, IATA | Void |
| · 14.5 Environmental hazards: · Marine pollutant: | No |
| · 14.6 Special precautions for user | Not applicable. |
| · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| · UN "Model Regulation": | Void |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **National regulations**
- **Water hazard class:**
Water hazard class 2 (Self-assessment): hazardous for water.
The classification based on german instructions.
- **15.2 Chemical safety assessment:**
A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H412 Harmful to aquatic life with long lasting effects.
- **Department issuing data specification sheet:** Environment protection department.
- **Contact:** Mr. Guido Herfort
- **Abbreviations and acronyms:**
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 8)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.05.2019

Version number 20

Revision: 06.05.2019

Trade name: Spezial-Faserbetonkleber Nr. 12/56 c (B-Komp.)

(Contd. of page 7)

IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

- * **Data compared to the previous version altered.**

GB